KRET SMOOTH

Kret Plaster · Burnished lime

M20 PLASTERED, RENDERED AND ROUGHCAST COATINGS

M20/105 KRET SMOOTH

Manufacturer	Kret Co., Ltd., Bangkok, Thailand · hello@kret.co.th
Product reference	Kret Plaster · Burnished lime
Product type	Lime-based decorative plaster, ready to use
Substrate	Plasterboard, render or sound plaster, primed
Primer	Kret Primer
System	2–3 coats, 0.5–1 mm each
Build	Thin coats, about 2 mm
Colour	Kret colour: [Code and name, for example MF-05 Yogurt White]
Finish	High sheen, polished
Protection	Wax, recommended in wet zones
Technical data	Kret technical data sheet KRET-TDS-001; safety data sheet KRET-SDS-001

210 SUPPLY AND APPLICATION

Requirement	Supply and apply by Kret Co., Ltd. using its own trained crews. No other applicator to be used.
Submittals	Data sheets, colour reference and programme before work starts.

220 SAMPLE PANEL

Size	Not less than 1 m², on the project substrate, in the specified colour and finish.
Approval	Obtain approval of the panel in site lighting before starting work. The approved panel is the standard for the whole installation. Retain until completion.

230 SUBSTRATE PREPARATION

Requirement	Sound, dry, clean, free of dust, grease, efflorescence and loose material.
New render or blockwork	Cured for at least 28 days.
Flatness	Within 3 mm under a 2 m straightedge before application.

240 ENVIRONMENTAL CONDITIONS

Temperature	+8 °C to +35 °C, air and substrate
Relative humidity	Below 85%
Protection	Protect from rain, direct sun and strong wind until dry.

250 APPLICATION

Method	In accordance with the Kret technical data sheet and the approved sample panel.
Joints	No visible joints or laps except at architectural breaks, corners or agreed stop lines.
Adjacent surfaces	Mask and protect. Remove splashes immediately.

260 COMPLETION

Inspection	Inspect with the contract administrator in normal lighting. Make good defects to match the approved sample.
Handover	Remove masking, clean down and hand over the Kret care and maintenance guidance.

Using this clause. Copy into the project specification and complete the bracketed items. Kret can supply an edited clause for your project on request: hello@kret.co.th