KRET RAMMED EARTH

Kret Clay · Rammed Earth

M20 PLASTERED, RENDERED AND ROUGHCAST COATINGS

M20/135 KRET RAMMED EARTH

Manufacturer	Kret Co., Ltd., Bangkok, Thailand · hello@kret.co.th
Product reference	Kret Clay · Rammed Earth
Product type	Layered clay and lime wall finish
Base	Kret Clay
Substrate	Render, blockwork or board, primed
Primer	Kret Primer
System	Layers of 3–5 mm to 15–20 mm
Build	15–20 mm, layered
Colour	Kret colourway: [RE-01 to RE-30]
Finish	Matt, as approved sample
Protection	Breathable sealer
Technical data	Kret technical data sheet KRET-TDS-007; safety data sheet KRET-SDS-007

210 SUPPLY AND APPLICATION

Requirement	Supply and apply by Kret Co., Ltd. using its own trained crews. No other applicator to be used.
Submittals	Data sheets, colour reference and programme before work starts.

220 SAMPLE PANEL

Size	Not less than 1 m², on the project substrate, in the specified colour and finish.
Approval	Obtain approval of the panel in site lighting before starting work. The approved panel is the standard for the whole installation. Retain until completion.

230 SUBSTRATE PREPARATION

Requirement	Sound, dry, clean, free of dust, grease, efflorescence and loose material.
New render or blockwork	Cured for at least 28 days.
Flatness	Within 3 mm under a 2 m straightedge before application.

240 ENVIRONMENTAL CONDITIONS

Temperature	+8 °C to +35 °C
Relative humidity	Below 85%
Protection	Protect from rain, direct sun and strong wind until dry.

250 APPLICATION

Method	In accordance with the Kret technical data sheet and the approved sample panel.
Joints	No visible joints or laps except at architectural breaks, corners or agreed stop lines.
Adjacent surfaces	Mask and protect. Remove splashes immediately.

260 COMPLETION

Inspection	Inspect with the contract administrator in normal lighting. Make good defects to match the approved sample.
Handover	Remove masking, clean down and hand over the Kret care and maintenance guidance.

Using this clause. Copy into the project specification and complete the bracketed items. Kret can supply an edited clause for your project on request: hello@kret.co.th