Kret Limewash · Brushed lime paint

LIMEWASH

Brushed lime paint. Soft, chalky and never flat.

Slaked lime and mineral pigment, brushed on in loose crossing strokes. Each coat dries a little differently, so the wall settles into a quiet, chalky cloud instead of a flat sheet of colour.



LIMEWASH · KRET, BANGKOK

COVERAGE	DRY TO TOUCH	PACKAGING
8–12 m²/L per coat, depending on the substrate	1–2 hours	5 L and 15 L pails

AREAS OF USE

- Walls
- Ceilings
- Built-in joinery

FEATURES

- Brushed, cloudy movement
- Finished in a day
- Walls, ceilings and joinery
- Breathable mineral paint
- Low in VOCs
- Easy to refresh with another coat

TECHNICAL DATA

PRODUCT TYPE	Mineral limewash paint, ready to use
COMPOSITION	Aged slaked lime, natural earth and mineral pigments, water
COLOUR	25 Kret colours, photographed
FINISH	Matt, brushed cloud
COATS	2–3, brushed
TOOLS	Block brush
AREAS OF USE	Walls, ceilings, built-in joinery

PROTECTION	Wax inside, sealer in wet and exterior areas
COVERAGE	8–12 m²/L per coat, depending on the substrate
DENSITY	1.25 ± 0.05 kg/L
PH	12.5–13
VOC CONTENT	< 1 g/L
REACTION TO FIRE	A2–s1, d0 (EN 13501–1)

APPLICATION CONDITIONS AND DRYING

MIXING	First coat: up to 10% clean water.
WORKING TIME	Ready to use. Stir often during use.
APPLICATION TEMPERATURE	+8 °C to +35 °C
RELATIVE HUMIDITY	Below 85%
DRY TO TOUCH	1–2 hours
RECOAT	6–12 hours
FULL CURE	14 days

Times given at 25 °C and 60% relative humidity. Lower temperatures and higher humidity lengthen them.

SURFACE PREPARATION

01 Substrate must be sound, clean and absorbent. Remove gloss and loose paint.

02 On non-mineral substrates, apply Kret Mineral Primer first and allow 6 hours.

03 Lightly dampen very absorbent surfaces before the first coat.

APPLICATION

01 Stir well. Apply with a wide block brush in loose, crossing strokes.

02 Work wet edge to wet edge, corner to corner, without stopping mid-wall.

03 Apply the second coat the same way once the first is dry. A third coat deepens the colour.

04 Colour lightens as it dries and settles over the first days.

AFTERCARE

- Protect from rain for 48 hours outdoors.
- In wet zones, seal with Kret Limewash Sealer when fully cured.

CLEANING AND MAINTENANCE

- Brushes in clean water straight after use.
- Dust with a soft brush. Touch up with the same batch.

PACKAGING AND STORAGE

PACKAGING	5 L and 15 L pails
SHELF LIFE	18 months in the unopened pail
STORAGE	Store sealed, upright, between +5 °C and +35 °C, out of direct sun. Do not freeze.

HEALTH AND SAFETY

- Contains lime or cement: alkaline. Causes serious eye damage and skin irritation.
- Wear gloves, eye protection and long sleeves. Wear a dust mask when mixing powders or sanding.
- Eyes: rinse at once with plenty of clean water for at least 15 minutes and seek medical advice.
- Keep out of reach of children. Do not empty into drains. See the safety data sheet.

Important. The values on this sheet are typical results from testing at 23 °C and 50% relative humidity. Site conditions, substrates and application affect the result, so final values are confirmed per project on the approved sample. Always trowel a sample panel on site before work begins. This issue supersedes all previous issues. **Kret Co., Ltd.** · Bangkok, Thailand · hello@kret.co.th